



# Belt Undercar Conveyors

24" Belt Width

Home of Worldwide Quality Blending, Conveying, Tending, & Spreading Products!



#304 Stainless  
Steel Conveyor  
Construction

Adjustable Axle  
Assembly for  
Ease of  
Handling

6', 8'  
Incline Sections  
Available



#304 Stainless  
Steel Incline  
and Transition  
Covers

UHMW Belt  
Hold Down  
Wheels

Totally  
Enclosed Belt  
Guard



## Doyle Equipment Mfg. Co., Inc.

4001 Broadway, P.O. Box 3024, Quincy, IL 62305

Toll Free: 800-788-8085 Fax: 217-223-3655

E-mail: [doyle@doylemfg.com](mailto:doyle@doylemfg.com) Web Site: [www.doylemfg.com](http://www.doylemfg.com)





## Standard Features:

- #304 stainless steel conveyor construction
- #304 stainless steel sealer strips
- #304 stainless steel motor mount
- #304 stainless steel enclosed discharge hood
- Rubber covered drive drum and steel return roller
- #304 stainless steel cover on transition and incline section
- Adjustable axle, for ease of handling
- Tires, with tubes & tail wheel
- Drive kit includes: belts, sheaves, bushings, & TEFC motor (Note: Conveyor ships with motor uninstalled)
- 8' flat x 8' incline x 24" wide belt uses 5 HP Motor
- 8' flat x 6' incline x 24" wide belt uses 5 HP Motor
- 6' flat x 6' incline x 24" wide belt uses 5 HP Motor
- Factory assembled & tested



## Optional Features:

- 4' flared intake hopper
- 4' flared intake hopper, with flow restrictor
- Stationary swivel mount for undercar conveyor

